	CONFIDENTIAL	_	25X1
TEGENSON OF THE PERSON OF THE		] 25X1	
	ć.		

existing longitudinal supports of the roadbed, two parallel sets of girders are to be put in. A representative of the bridge section of the railroad directorate in Schwerin (M 54/T 46) went to Berlin on 27 Becember 1949 to discuss this plan.

- 4. On 29 December 1949 it was learned that the steel work order will be given to the Nordstahl Firm in Restock (M 55/0 81), and the wood, stone, and excavation work order to the Kommunale Baubetriebe Firm in Perleberg (M 5h/T 70). The costs were estimated at 1h0,000 DM. The date of completion was set as 31 January 1950.
- 5. Soviet officers surveyed the widening of the roadbed of the Elbe bridge near mittenberge which will be started soon. On 8 January 1950, German workers who had been given this dismissal notices were told that the notices were withdrawn and they would start work on 9 January 1950. The roadbed is to be made serviceable for Soviet tanks. The roadbed was to be widened by shortening the stiffeners which support and stabilize the girders. The stiffener on each side was to be shortened 30 cm which will widen the roadbed 60 cm. However, German experts pointed out that this would mean a reduction in the load capacity of the bridge, but the Soviets insisted on a load capacity of 75 tons. Soviet officers remarked that the heaviest tanks would have to cross the bridge one at a time.
- 6. The work on the roadbed was checked by a colonel from the road administration in Karlshorst on 17 March 1950. He ordered the work to be completed by 31 March 1950, but later 15 April 1950 was agreed upon as the date of completion. On 17 March 1950 the flood water spans of the bridge, and the two "R"(Roth) military bridge spans were complete and the old steel spans were 45 percent completed.
- 7. On 1 April 1950 it was learned that work involved in widening the roadbed of the Elbe bridge was still in progress and was 70 percent complete. Daily reports on the progress of the work had to be made to the Kommadatura in Perleberg (M 5h/ T 70).
- 8. On 15 April 1950 the completed roadbed was 360 cm wide. The widening was completed except for laying about 400 wooden reinforcement ties which are to be used instead of the sets of longitudinal girders which are not available.
- 9. On 13 June 1950 it was learned that the Elbe bridge had been widened 40 cm by order of the Soviet commanding officer. This was done by shortening the stiffeners. Heavy tanks can now pass over the bridge.
- 10. On 17 July 1950 the reinforcement of the readbed, which was widened to 360 cm, was almost complete. Four hundred and twenty new reinforcement ties, 2\(\text{Lx2\lpha}\) cm, each \(\text{L}\) meters long, were inserted in every second tie section. The total cost of the work was about 280,000 DM. The completion of the work was delayed by a lack of split nails. Between 60,000 and 80,000 of these, which are from \(\text{L}\)-mm sheet iron, were required. The paving at the section connecting with the Wittenberge road was about 80 percent complete. \*

,	Comment. For sketch of the two designs see innex. Information on the
1	and road bridge across the Elbe River near Jittenberge, the widening of the rebed which has been planned since late 1949, was previously submitted.
	Since the rough this bridge was only 300 cm wide it could not be used by the heaviest Soviet which are 320 cm wide. The first design to widen the roadbed provided for little the roadbed planking over the stiffeners. The roadbed was finally widened to 360 cm by shortening the stiffeners. This measure, however, reduced the stable of the braces of the bridge and required the insertion of reinforcement ties. The road crossing near littenberge is a section of Reichsstrasse No 189. It is the conly road bridge in the libe River section between Tangermuende and Doemitz, with a distance of about 100 km.

CONFIDENTIAL 25X1